



Compressor  
Voltage Code : FZ

CAJ4517T-FZ

High Temp. Commercial (HP)

220 - 240V 1~ 50 Hz

R22

AJ4517T-FZ3C

Operating conditions : <b>Customized... / 50 Hz / Dew</b>		Sound Power ISO3745 / ISO 3743-1
Evaporating Temp. : -10.0 °C	Refrig. Capacity : 2046 Watt	
Superheat : 10.0 K		
Return gas temp. : 10.0 °C	Power Input : 1004 Watt	
Condensing Temp. : 45.0 °C	Amps : 4.64 A	
Subcooling : 10.0 K	C.O.P : 2.04 Watt/W	
Liquid : 34.7 °C		
Displacement (cc)		25.95
Net Weight (Kg)		23.3
Oil Quantity (cc)		475.0
Oil Type		Mineral
Expansion Device		Capillary_Tube/Expansion_Valve
Cooling		Fan
Main Winding (Ohm)		1.6
Start Winding (Ohm)		6.5
Current		
RLA (A)		6.1
MCC (A)		10
LRA (A)		35
Electrical Equipment		CSR
Overload		MRA38124
Time Check		2.8s - 5.2s / 29.5 A
Open Temp		105° C
Close Temp		57° C
Optional		T0796
Start Capacitor		20 µF / 400 V
Run Capacitor		100 µF / 330 V
Potential Relay		RVA6M**
Pick Up		239/268V
Drop Out		60/135V
Optional		3ARR3*4AA*
Refrigerating connection for OD		
Suction Tube		15.9 (5/8")
Discharge Tube		9.5 (3/8")
Process Tube		6.35 (1/4")

Certificates :



Note : Tecumseh reserves the right to change information contained in this document without notification.

<b>CAJ4517T-FZ</b>	<b>Tension FZ : 220 - 240V 1~ 50 Hz</b>
--------------------	---

Les performances sont données dans les <b>conditions EN12900</b> :	Gaz aspirés :	20.0 °C
Condition Dew	Sous refroidissement :	0.0 K
The performance data are in <b>EN12900 conditions</b> :	Return gas :	20.0 °C
Dew Condition	Subcooling :	0.0 K

<b>50 Hz R22</b>										
										<b>N°234LT-FZ</b>

4   T condensation	5   T évaporation	(°C)	<b>-20</b>	<b>-15</b>	<b>-10</b>	<b>-5</b>	<b>0</b>	<b>5</b>	<b>10</b>	<b>15</b>
<b>40</b>	1   P frigorifique	(Watt)	1264	1706	2205	2758	3364	4020	4725	5477
	2   P absorbée	(W)	829	913	991	1062	1127	1185	1237	1282
	3   I absorbée	(A)	3.81	4.24	4.62	4.97	5.26	5.52	5.73	5.90
<b>50</b>	1   P frigorifique	(Watt)	982	1369	1807	2293	2826	3403	4022	4681
	2   P absorbée	(W)	780	904	1018	1123	1217	1301	1376	1440
	3   I absorbée	(A)	3.58	4.14	4.66	5.13	5.56	5.95	6.29	6.58
<b>60</b>	1   P frigorifique	(Watt)		1012	1396	1822	2288	2793	3332	3905
	2   P absorbée	(W)		894	1045	1183	1308	1419	1517	1601
	3   I absorbée	(A)		4.06	4.71	5.31	5.87	6.38	6.84	7.27
