

## ***GAS SEEKER® GS30 - Portable Combustible Gas Detector***

The **GS30** is a low maintenance, easy-to-use portable combustible gas leak detector engineered to pinpoint leaks in residential, commercial and industrial appliances. Advanced semiconductor sensor and electronic control package enables detection of gases commonly found in service applications including; Carbon Monoxide, Natural Gas, Propane, Ammonia, Methane, Acetone, Hydrogen and Iso-Butane, with a virtually instantaneous alarm response period. Measuring just over 7" long and 0.72" in diameter its compact tubular shape enables testing in limited access areas and conveniently fits into a serviceman's pocket. Applications include the inspection of furnaces, valves, regulators, pipelines, meters and other devices associated with combustible gases.



### ***Gases Detected***

*Carbon Monoxide, Natural Gas, Propane, Ammonia, Methane, Acetone, Hydrogen, Iso-Butane Acetone, Acetylene, Benzene, Butane, Ethanol, Ethylene Oxide, Gasoline, Hexane, Industrial Solvents, Paint Thinners, and Naptha.*

**WARNING: THE GS30 IS NOT INTRINSICALLY SAFE IN CLASS 1 (EXPLOSIVE) TYPE ATMOSPHERES AND IS NOT SUITABLE FOR THE DETERMINATION OF HUMAN SAFETY OR HABITABILITY CONDITIONS.**

Detecting Range	<b>0 - 100% LEL referenced to Methane.</b>
Alarm Indication	<b>Both visual and audible (&gt;40db) alarm indicators</b>
Low Level Alarm	<b>Preset at 10% LEL.</b>
High Level Alarm	<b>Preset at 30% LEL</b>
Operating Conditions	<b>0°F to 104°F / -20°C to +40°C at less than 98% RH (non-condensing)</b>
Power	<b>Working voltage is 3VDC using two 1.5V AA batteries.</b>
Battery Life/Indicator	<b>5 hrs continuous use. Orange LED constantly illuminates when battery is low</b>
Sampling	<b>Natural diffusion</b>
Dimensions	<b>7.2 x 0.71in / 183 x 18mm</b>
Weight	<b>5.3oz / 150g (including battery)</b>